



# TECHNICAL DATA SHEET

## 50 ohm Connectors for RF Cables

Kabelwerk | **EUPEN** AG

Rev.: 11/2023-10-12

cable

### Connector 7/8" for EC5-50-A (5228A) and EA5-50 (5227)

#### FEATURES

- **Low reflection coefficient (up to 3.0 GHz)**
- **Low PIM level**
- **High contact force through inner contacts made in a high-strength copper alloy**
- **Watertight (IP67/IP68)**
- **Corrosion resistant**
- **Quick trimming tool for cable preparation**
- **Fully compatible with copper & aluminium cable**



The connectors are designed according the standard interfaces as N, DIN 7-16 or 4.3-10. Contact components are silver or trimetal plated to minimize insertion loss and passive intermodulation products; mechanical parts are nickel plated for heavy-duty handling and best corrosion resistance. Watertightness is achieved by using silicone o-rings to resist in the toughest environmental conditions. For a cost effective, easy and reliable installation, special trimming tools are recommended.

#### SPECIFICATIONS

Connector type	N-male	N-female	4.3-10 male	4.3-10 female	7-16 male	7-16 female
<b>Electrical specifications</b>						
• Nominal impedance [ $\Omega$ ]				50		
• Reflection coefficient @ 3.0 GHz [dB]				$\geq 35$		
• Insulation resistance [G $\Omega$ ]		$\geq 5$				$\geq 10$
• Test voltage (at sea level) [kV rms, 50Hz]		2.5				4
• Working voltage (at sea level) [kV rms, 50Hz]		1				2.7
• Max. peak power [kW]	10			15*		40
• Screening effectiveness up to 1 GHz [dB]				$> 128$		
• Contact resistance (outer contact) [m $\Omega$ ]				$\leq 1$		
• Contact resistance (inner contact) [m $\Omega$ ]				$\leq 1$		
• PIM ratio (2 x 20 W carrier) [dBc]				$\leq -155$ (Typical -163)		
<b>Mechanical specifications</b>						
• Torque of coupling mechanism [Nm]	3 to 5			5 to 8		30
• Tensile strength of coupling mechanism [N]	400			500		700
• Cable retention [N]				$> 1000$		
• Mechanical endurance (Nr of couplings)				$\geq 500$		
• Outer diameter [mm]				35		
• Length [mm]	62	57	57	56	53	52
• Weight [g]	164	153	171	160	170	160
<b>Environmental specifications</b>						
• Temperature range	-40 °C to +85 °C (-40 °F to +185 °F)					
• Degree of protection	IP67/IP68 (mated connectors)					
• Climatic & moisture resistance test	acc. ANSI/SCTE 72 2002 R2007 (-40 °C / +60 °C @ 75% r.h.) for 2 weeks					
• Corrosion resistance test	acc. IEC 60068-2-11-Test Ka					
• Vibration test	acc. IEC 60068-2-6 (10 to 500 Hz @ 10 G)					
<b>Materials</b>						
• Externals parts	Brass with passivated silver or trimetal or nickel plating					
• Outer contact	Brass with passivated silver or trimetal plating					
• Inner contact	Passivated silver plated high-strength copper alloy and brass					
• Dielectric	TPX					
• O-rings	High quality silicone					
<b>Cable dimensions [mm]</b>						
• Inner conductor inner diameter	8.26 to 8.46					
• Outer conductor outer diameter	24.6 to 25.4					
• Jacket outer diameter	27.8 to 28.2					
<b>Order codes</b>						
• O-ring connector type	NM50V78N1	NF50V78N1	43MV78N1	43FV78N1	716MV78N1	716FV78N1
• Special trimming tool	F-78					

\* ambient temperature 90 °C max.