



TECHNICAL DATA SHEET

50 ohm Connectors for Radiating Cables

Kabelwerk | **EUPEN** AG

Rev.: 03/2019-05-21

cable

Connectors for EUCARAY® RC400 radiating cables

FEATURES

- **High contact force and inner contacts made in a high-strength copper alloy**
- **Watertight (IP67/IP68)**
- **Corrosion resistant**
- **Quick trimming tool**
- **Installation "fit on and tighten it"**



NF50RC400

NM50RC400

The connectors are designed according to the standard interfaces as N. Contact components are silver plated to minimize insertion loss; mechanical parts are nickel plated for best corrosion resistance. The special quick trimming tool makes installation very easy and cost effective in time.

SPECIFICATIONS

Connector type	N-male	N-female
Electrical specifications		
• Nominal impedance [Ω]		50
• Reflection coefficient @ 3 GHz / 6 GHz [dB]		≥ 35 / ≥ 30
• Insulation resistance [$G\Omega$]		≥ 5
• Test voltage (at sea level) [kV rms, 50Hz]		2.5
• Working voltage (at sea level) [kV rms, 50Hz]		1
• Contact resistance (outer contact) [$m\Omega$]		≤ 2
• Contact resistance (inner contact) [$m\Omega$]		≤ 2
Mechanical specifications		
• Torque of coupling mechanism [Nm]		8
• Tensile strength of coupling mechanism [N]		400
• Cable retention [N]		> 400
• Mechanical endurance (Nr of couplings)		≥ 500
• Length [mm]	53	52
• Weight [g]	51	47
Environmental specifications		
• Temperature range	-40 °C to +65 °C (-40 °F to +149 °F)	
• Degree of protection	IP67/IP68 (mated connectors)	
Materials		
• Externals parts	Passivated silver plated or electroless nickel plated brass	
• Outer contact	Passivated silver plated brass	
• Inner contact	Passivated silver plated high-strength copper alloy and brass	
• Dielectric	PTFE or TPX	
• Gaskets	High quality silicone & nitrile	
Tool codes		
	SPTC50RC400	
Connectors codes		
	NM50RC400	NF50RC400