



DATA SHEET TORQUE WRENCHES

Kabelwerk | **EUPEN** AG

Rev.: 02/2016-09-07

cable

Preset Torque Wrenches

The torque wrenches emit an audible 'click' when the specified torque is reached. Proper tightening ensures watertightness and prevents loosening from vibration.

Blue Wrench Handles for connector back nuts

Reference	Connector	Size mm (in)	Head thickness mm	Torque value Nm (ft-lb)	Part #
TQ-34-F20	1/2" & 1/2" Hiflex	19 (3/4")	7	27 (20)	G551996
TQ-30MM-F22	7/8" & 7/8" Hiflex	30	12	30 (22)	E937996
TQ-11116-F29	1-1/4" & 1-1/4" Hiflex	43 (1-11/16")	13	40 (29)	E938996
TQ-214-F37	1-5/8"	58 (2-14")	13	50 (37)	E939996

Important: Hold connector body fixed while turning back nut with torque wrench.



Red Wrench Handles for connector interfaces

Reference	Connector	Size mm (in)	Head thickness mm	Torque value Nm (ft-lb)	Part #
TQ-114-F18-M	7-16 DIN coupling nut	32 (1-1/4")	13	25 (18)	E941996
TQ-78-F6-M	4.3 - 10 coupling nut	22 (7/8")	10	8 (6)	M816996

