



## PE-HDPE Underground cable ducting pipes for buried cables

according to

**NBN EN61386-24; DIN16961**



| DN  | Outside diameter in mm | Inside diameter in mm | Bending radius in m. | Weight in kg/m |
|-----|------------------------|-----------------------|----------------------|----------------|
| 40  | 40                     | 32                    | 0,35                 | 0,134          |
| 50  | 50                     | 40                    | 0,35                 | 0,188          |
| 63  | 64                     | 52                    | 0,35                 | 0,240          |
| 75  | 76                     | 62                    | 0,35                 | 0,304          |
| 90  | 91                     | 75                    | 0,35                 | 0,440          |
| 110 | 111                    | 93                    | 0,50                 | 0,540          |
| 125 | 126                    | 107                   | 0,50                 | 0,712          |
| 160 | 161                    | 138                   | 0,75                 | 0,980          |
| 200 | 200                    | 176                   | 1,00                 | 1,450          |

|                                  |   |
|----------------------------------|---|
| <b>Provisional puller wire :</b> | Maximum pulling force 200N  |
| <b>Materiel :</b>                | PE-halogen free   |
| <b>Connection type :</b>         | PE sleeve type SD (sand-tight)  |
| <b>Roll length :</b>             | 25 and 50 m   |
| <b>Colour :</b>                  | Black, red or blue - other colours on request (for example green, yellow) |

All information given is indicative only and not binding and can be subject to change without notice.